


Lite Lion products including DMX series, DALI series, WIFI series, Intelligent electric series, Dimmer series, RF series, dream color series, indoor and outdoor lighting control system series etc. Please kindly contact us for more details and we will reply a.s.a.p.

<p>Full color touch controller</p> 	<p>Working temperature: -20-60℃ Supply voltage: DC12-24V External dimension: L85*W45*H23 mm Packing size: L105*W65*H43 mm Carton size: L500*W275*H310mm Net weight: 297g Gross weight: 382g Output: 3 channels Output current: ≤8A(each channel) Static power consumption: <1W Connecting mode: common anode Output power: 12V<288W, 24V<576W</p> <p>Model: RF800</p>
<p>RGBW 4CH controller</p> 	<p>Working temperature: -20-60℃ Supply voltage: DC 12-24V Output voltage: DC 12-24V Output connect way: common anode (6 line with 4 loop) External dimension: L76.6*W59*H22.2 mm Packing size: L103*W70*H43 mm Net weight: 133g Gross weight: 152g Remote control static state current: <10uA Maximum output current : 4*4A Maximum output power: 12V<192W, 24V<384W Remote control distance: ≤25M</p> <p>Model: RF104</p>
<p>Wireless high voltage RGB controller</p> 	<p>Work temperature: -20-60℃ Supply voltage: AC90-240V Size: L132*W45*H24mm Package size: L140*W55*H35mm Carton size: L500*W275*H310mm Net weight: 90g Gross weight: 160g Output: 3 Channels Output current: <1A(each channel) Static power: <1W Connecting mode: common anode Output power: AC110V:<330W, AC220V:<660W</p> <p>Model: RF700</p>
<p>2.4G controller</p>	<p>Working temperature: -20-60 °C Supply voltage: DC5 -24V</p>

	<p>Size: L120*W62*H24 mm Package size: L185*W145*H52mm Net weight: 226g Gross weight: 320g Output: 3 channels Output current : <8A(each channel) Static power consumption: <1W Connecting mode: common anode Output power: 5V<180 W, 12V< 288W, 24V<576 W Function: 2.4G controller is our newly wireless high power LED controller. Equipped with touch remote , touch remote with high precision capacitance touch control technology, combined with the use of touch color ring, can choice color you need with one key, convenient and quick. Each controller only one address code, in order to prevent to control chaos caused by repeated code control. Each controller can also equipped with four remote, can realize many controller synchronous control.</p> <p>Model: RF201</p>
<p>2.4G color temperature controller</p> 	<p>Working temperature: -20-60 °C Supply voltage: DC5V -24V Size: L120*W62*H24 mm Package size: L185*W145*H52mm Net weight: 220g Gross weight: 314g Output: 2 channel Output current : <8A(each channel) Static power consumption : <1W Connecting mode: common anode Output power: 5V<80 W, 12V< 192W, 24V<384 W Function: 2.4 G controller is our newly wireless high power LED controller. Equipped with touch remote , touch remote with high precision capacitive touch control technology, combined with the use of touch color ring, can choice color you need with one key, convenient and quick. Each controller only one address code, in order to prevent to control chaos caused by repeated code control. Each controller can also equipped with four remote, can realize many controller synchronous control.</p> <p>Model: RF202</p>

<p>Touch 5key full color controller</p> 	<p>Working temperature:-20-60 °C Supply voltage: DC12-24V Size: L84*W64*H23 mm Package size: L200*W146*H36mm Net weight: 150g Gross weight: 200g Output: 3 channels Output current : <6A(each channel) connection mode: common anode Static power consumption: <1W Output power: 12V< 180W, 24V<360W</p> <p>Model: RF301</p>
<p>Touch controller-8key</p> 	<p>working temperature: -20-60℃ supply voltage: DC12V-24V external dimension: L108*W42*H27mm packing size: L135*W135*H50mm net weight: 130g gross weight: 165g output: 3 channels output current: <4A(each channel) static power consumption: <1W connection mode: common anode output power: 12V:<144W, 24V:<288W</p> <p>Model: CON-TRF8B(T)-3CH</p>
<p>Touch controller-8key</p> 	<p>working temperature: -20-60℃ supply voltage: DC12V-24V external dimension: L130*W64*H24mm packing size: L137*W137*H51mm net weight: 119g gross weight: 262g output: 3 channels output current: <4A(each channel) static power consumption: <1W connection mode: common anode output power: 12V:<144W, 24V:<288W</p> <p>Model: CON-TRF8B(H)-3CH</p>
<p>Touch controller-8key</p>	<p>working temperature: -20-60℃</p>

	<p>supply voltage: DC12V-24V external dimension:'L63*W35*H22mm packing size: L105*W65*H40mm net weight: 50g gross weight: 70g output: 3 channels output current: <2A(each channel) connection mode: common anode static power consumption: <1W output power: 12V:<72W, 24V:<144W</p> <p>Model: CON-TRF8B(J)-3CH</p>
<p>Wireless Controller</p> 	<p>Work temperature: -20-60℃ Supply voltage: DC12-24V Size: L108*W76*H43mm Package size: L145*W95*H50mm Net weight:140g Gross weight: 175g Output: 3 channel Static power: <1W Output current: <3A(each channel) Connecting mode: common anode Output power: 12V:<108W, 24V:<216W</p> <p>Model: CON-RF20B(FS)-3CH</p>
<p>24-key Infrared Controller (NEW)</p> 	<p>Working temperature: -20-60 ℃ Supply voltage: DC12-24V Size: L63*W35*H22mm Packing size : L105*W65*H40mm Carton size: L500*W275*H310mm Net weight: 50g Gross weight: 70g Output: Three CMOS drain open-circuit output Connecting mode: common anode Advantages: With output load short circuit protection function, with set the line sequence (RGB, RBG, GRB, GBR, BRG, BGR) function, all of the brightness and the speed is adjustable With the specified color selection function With control lock function Output current: <2A (each channel) Static power consumption: <1W Output power: 12V: <72W, 24V: <144W</p> <p>Model: IR240</p>
<p>44-key Infrared Controller(NEW)</p>	<p>Working temperature: -20-60 ℃ Supply voltage: DC12-24V Controller size: L63*W35*H22mm Remote size: L125*W56*H7mm Packing size : L130*W60*H35mm</p>

	<p>Carton size: L500*W275*H310mm Net weight: 60g Gross weight: 90g Output: Three CMOS drain open-circuit output Connecting mode: common anode Advantages: With output load short circuit protection function, with set the line sequence (RGB, RBG, GRB, GBR, BRG, BGR) function, all of the brightness and the speed is adjustable With the specified color selection function With control lock function Output current: <2A (each channel) Static power consumption: <1W Output power: 12V: <72W, 24V: <144W Model:IR440</p>
---	---