




Lite Lion (HK) Trading Limited

Lite Lion products including DMX series, DALI series, WIFI series, Intelligent electric series, Dimmer series, RF series, dream color series, indoor and outdoor lighting control system series etc. Please kindly contact us for more details and we will reply a.s.a.p.

<p>Rotary knob RGB controller</p>  A square, silver-colored rotary knob controller. It features a central circular knob with a rainbow-colored arc on its top half. The knob has 'M-' on the left and 'M+' on the right. Below the knob are two small arrows, one pointing left and one pointing right.	<p>working temperature: -20-60 °C      supply voltage: DC12V~24V output: 3 channel external dimension: L86*W86*H37 mm packing size: L90*W90*H50 mm net weight: 185g gross weigh: 215g static power consumption: &lt;1W output current: &lt;4A/CH output power: 12V:&lt;144W, 24V:&lt;288W <b>MODEL:TM01</b></p>
<p>Touch panel RGB controller</p>  A white, rectangular touch panel controller. It has a circular touch area in the center with a rainbow-colored arc. Above the circle are three small icons: a square, a circle, and a triangle. Below the circle are three small colored dots: red, green, and blue. There are also two small arrows on the right side.	<p>working temperature: -20-60 °C      supply voltage: DC12V~24V output: 3 channel      connect way: common anode external dimension: L86*W86*H37 mm packing size: L90*W90*H50 mm net weight: 185g gross weigh: 215g static power consumption: &lt;1W output current: &lt;4A/CH output power: 12V:&lt;144W, 24V:&lt;288W <b>MODEL:TM02</b></p>
<p>Touch Panel hand dimmer</p>  A white, rectangular touch panel hand dimmer. It has a square touch area in the center with a circular icon. There are also two small arrows on the right side.	<p>working temperature: -20-60 °C      supply voltage: DC12V~24V external dimension: L86*W86*H34 mm packing size: L122*W85*H42mm net weight: 100g gross weigh: 130g output current: &lt;8A Output: 1 channel output power:5V&lt;40W 12V:&lt;96W, 24V:&lt;192W <b>Model:TM04</b></p>

<p>Touch Panel 3 keys dimmer</p>  A square yellow touch panel with a black circular area in the center containing three icons: a sun, a moon, and a flame.	<p>working temperature: -20-60 °C      supply voltage: DC12V~24V external dimension: L86*W86*H37 mm packing size: L122*W85*H42 mm net weight: 100g gross weight: 130g static power consumption: &lt;1W output current: &lt;8A output power: 5V&lt;40W 12V:&lt;96W, 24V:&lt;192W <b>Model:TM05</b></p>
<p>Touch Panel Color Temperature controller</p>  A square white touch panel with a yellow circular slider in the center, flanked by two arrows pointing left and right.	<p>working temperature: -20-60 °C      supply voltage: DC12-24V external dimension: L86*W86*H36 mm packing size: L115*W110*H56 mm net weight: 130 g      gross weight: 187g      output::2 channels static power consumption: &lt;1W output current: &lt;4A( each channel ) output power: 12V:&lt;96W, 24V:&lt;192W <b>MODEL:TM07</b></p>
<p>Low voltage panel dimmer</p>  A square white touch panel with a black circular slider in the center, flanked by two arrows pointing left and right.	<p>working temperature:-20-60℃      supply voltage:DC12-24V external dimension:L86×W86×H36mm packing size: L115×W110×H56mm net weight: 130 g      gross weight: 187g output::1 channels      static power consumption: &lt;1W output current: 5A( each channel ) output power: 12V&lt;60W, 24V&lt;120W <b>MODEL:TM06A</b></p>
<p>RGB touch panel controller</p>  A square white touch panel with a circular color wheel in the center, featuring a rainbow spectrum of colors.	<p>working temperature:-20-60℃      supply voltage:DC12-24V external dimension:L86×W86×H36mm packing size: L115×W110×H56mm net weight: 130 g      gross weight: 187g output::3 channels      static power consumption: &lt;1W output current: 5A( each channel ) output power: 12V&lt;180W, 24V&lt;360W <b>MODEL:TM08A</b> <b>With remote:</b></p>

	<b>Without remote:</b>
<p>RGBW controller</p> 	<p>1.2.4G, touch panel is a receiver, add a remote by partition; can add WIFI-2.4G, network packet realize packet controlle and synchronization control; 3.supply voltage:DC12-24V 4.output current: 5A( each channel )</p> <p><b>MODEL:TM201</b></p>
<p>Touch panel music controller</p> 	<p>working temperature: -20-60 °C      supply voltage: DC12-24V external dimension: L86*W86*H36 mm packing size: L115*W110*H56 mm Carton size: L500*W275*H310mm net weight::101g      gross weight: 161g Output: 3 channels      static power consumption: &lt;1W Output current: &lt;4A ( each channel ) Output power: 12V:&lt;144W, 24V:&lt;288W</p> <p><b>MODEL: TM14</b></p>
<p>Voice controller</p> 	<p>Function:can recognize the humans voices, complete the required state, such as switches, static and dynamic mode switching; supply voltage:DC12-24V output current: 5A( each channel )</p> <p><b>MODEL:TM10B3</b></p>

gesture-sensing control panel



Working temperature: -20-60 °C      Supply voltage: DC12V-24V  
Size: L86\*W86\*36.7mm      Package size: 105\*105\*53mm  
Net weight: 123.3g      Gross weight: 177g  
Static power consumption: <1W  
Gesture-sensing distance: 0-5cm  
Output current: <2A/CH    Output power: 12V:<72W, 24V:<144W  
**Features:** It adopts gesture-sensing control chip, no need to touch, just certain gesture can control output.  
Range of application: hospital, kitchen, washroom, garage, and some public places in which do not need to contact the panel directly.

**Model: FS01**


Touch Panel Controller  
(4 channel)



working temperature: -20-60 °C      supply voltage: DC12-24V  
external dimension: L86\*W86\*H36 mm  
packing size: L115\*W110\*H56 mm  
net weight: 131 g      gross weight: 183g      output: 4 channels  
static power consumption: <1W  
output current: <4A ( each channel )  
output power: 12V:<192W, 24V:<384W

**MODEL: TM09**

DALI touch scene panel



Working temperature: -20-60°C      Power supply voltage: AC90-260V  
External dimension: L86\*W86\*H36 mm  
Packing size: L115XW110XH56mm  
Net weight: 139.5g      Gross weight: 200g  
Output connect way: common cathode  
Output signal: 8 channel 5V switching signal  
Static power consumption: <1W

**Model: DL104**

<p>WIFI touch dimmer (output 0-10V)</p> 	<p>Working temperature: -20-60 °C Supply voltage: AC90-240V (50Hz/60Hz) External dimension: L86*W86*H37 mm Package size: L112*W115*H60 mm Carton size: L500*W275*H310 mm Net weight: 160g      Gross weight: 221g Max current of signal output: 15mA Static power consumption: &lt;3W</p> <p><b>Model: TM113</b></p>
<p>WIFI triac touch dimmer</p> 	<p>Working temperature: -20-60°C Power supply voltage: AC90-240V (50Hz/60Hz) External dimension: L86*W86*H37 mm Packing size: L90 * W90* H40 mm Carton size: L500*W275*H310mm Net weight: 160g      Gross weight: 221g Output signal: 1 channel phase control output Static power consumption: &lt;2W Output current: &lt;200W:</p> <p><b>Model: TM111</b></p>
<p>Touch Panel 0-10V Output Dimmer</p> 	<p>Working temperature: -20-60°C Power supply voltage: AC90-240V (50Hz/60Hz) External dimension: L86*W86*H36 mm Remote size: L119.7*W43.2*H16.4 mm Packing size: L195*W155*H60 mm Carton size: L500*W275*H310 mm Net weight: 154g      Gross weight: 263g Output signal : 0-10V signal Max current of signal output: 15mA Static power consumption: &lt;3W</p> <p><b>Model: TM016</b></p>

European standard touch dimmer (output 0-10V)



Working temperature: -20-60℃  
Power supply voltage: AC90-240V (50Hz/60Hz)  
External dimension: L80\*W80\*H42 mm  
Packing size: L105\*W105\*H53 mm  
Carton size: L500\*W275\*H310 mm  
Net weight: 144g Gross weight: 194g  
Output signal : 0-10V signal  
Max current of signal output: 15mA  
Static power consumption: <3W  
**Model: TM120E**

**European standard series**

Low-voltage dimmer (European standard)



working temperature: -20-60 ℃ supply voltage: DC12V~24V  
external dimension: L80\*W80\*H41.8 mm  
packing size: L105\*W105\*H53 mm  
Carton size: L500\*W275\*H310mm  
net weight: 127 g gross weigh: 177g  
output: 1 channel static power consumption: <1W  
output current: <8A  
output power: 12V:<96W, 24V:<192W

**MODEL: TM06E**

Touch Dimmer with remote (European standard)



working temperature: -20-60 ℃ supply voltage: DC12V~24V  
external dimension: L80\*W80\*H41.8 mm  
packing size: L185\*W145\*H55 mm  
Carton size: L500\*W275\*H310mm  
net weight: 150.7 g gross weigh: 217.2g  
Connecting mode: common anode Working frequency: 1KHz  
output: 1 channel static power consumption: <1W  
output current: <8A output power: 12V:<96W, 24V:<192W

**MODEL: TM062E**

Low-voltage Color Temperature controller (European standard)

working temperature: -20-60 ℃ supply voltage: DC12V~24V  
external dimension: L80\*W80\*H41.8 mm  
packing size: L105\*W105\*H53 mm  
Carton size: L500\*W275\*H310mm  
net weight: 128g gross weigh: 178g

	<p>output: 2 channels                      static power consumption: &lt;1W output current: &lt;4A (each channel) output power: 12V:&lt;96W, 24V:&lt;192W</p> <p><b>MODEL: TM07E</b></p>
<p>Color Temperature controller with remote (European standard)</p> 	<p>working temperature: -20-60 °C                      supply voltage: DC12V~24V external dimension: L80*W80*H41.8 mm packing size: L185*W145*H55 mm net weight: 150.7 g                      gross weigh: 217.2g Carton size: L500*W275*H310mm Connecting mode: common anode    Working frequency: 1KHz output: 2 channels                      static power consumption: &lt;1W output current: &lt;4A(each channel) output power: 12V:&lt;96W, 24V:&lt;192W</p> <p><b>MODEL: TM072E</b></p>
<p>Low-voltage full-color controller (European standard)</p> 	<p>working temperature: -20-60 °C                      supply voltage: DC12V~24V external dimension: L80*W80*H41.8 mm packing size: L105*W105*H53 mm Carton size: L500*W275*H310mm net weight: 130 g                      gross weight: 181g output: 3 channels                      static power consumption: &lt;1W output current: &lt;4A (each channel) output power: 12V:&lt;144W, 24V:&lt;288W</p> <p><b>MODEL: TM08E</b></p>
<p>full-color controller with remote (European standard)</p> 	<p>working temperature: -20-60 °C                      supply voltage: DC12V~24V external dimension: L80*W80*H41.8 mm packing size: L185*W145*H55 mm Carton size: L500*W275*H310mm net weight: 150.7 g                      gross weigh: 217.2g Connecting mode: common anode Working frequency: 1KHz output: 3 channels                      static power consumption: &lt;1W output current: &lt;4A (each channel) output power: 12V:&lt;144W, 24V:&lt;288W</p> <p><b>MODEL: TM082E</b></p>



<p>Low-voltage full-color controller (European standard)</p> 	<p>working temperature: -20-60 °C      supply voltage: DC12V~24V external dimension: L80*W80*H41.8 mm packing size: L105*W105*H53 mm Carton size: L500*W275*H310mm net weight: 127 g      gross weigh: 177g output: 3 channels      static power consumption: &lt;1W output current: &lt;4A (each channel) output power: 12V:&lt;144W, 24V:&lt;288W <b>MODEL: TM08E2</b></p>
<p><b>American standard series</b></p>	
<p>Low-voltage dimmer (American standard)</p> 	<p>working temperature: -20-60 °C      supply voltage: DC12V~24V external dimension: L74*W120*H42 mm packing size: L145*W99*H53 mm net weight: 151g gross weigh: 208g output: 1 channel static power consumption: &lt;1W output current: &lt;8A output power: 12V:&lt;96W, 24V:&lt;192W <b>MODEL: TM06U</b></p>
<p>Low-voltage Color Temperature Controller (American standard)</p> 	<p>working temperature: -20-60 °C      supply voltage: DC12V~24V external dimension: L74*W120*H42 mm packing size: L145*W99*H53 mm net weight: 127 g      gross weigh: 177.5g output: 2 channels      static power consumption: &lt;1W output current: &lt;4A (each channel) output power: 12V:&lt;96W, 24V:&lt;192W <b>MODEL: TM07U</b></p>
<p>Low-voltage full-color controller (American standard)</p>	<p>Working temperature: -20-60 °C      supply voltage: DC12V~24V external dimension: L74*W120*H41.8 mm packing size: L145*W99*H53 mm net weight: 159.1g gross weight: 216.7g output: 3 channels static power consumption: &lt;1W</p>



 A black rectangular touch dimmer switch with a circular color wheel and a power button.	<p>output current: &lt;4A (each channel) output power: 12V:&lt;144W, 24V:&lt;288W <b>MODEL: TM08U</b></p>
<p>America standard touch dimmer (output 0-10V)</p>  A black rectangular touch dimmer switch with a vertical slider and a power button.	<p>working temperature: -20-60℃ Power supply voltage:AC90-240V (50Hz/60Hz) External dimension: L74*W120*H42 mm Packing size: L145*W99*H53 mm Carton size: L500*W275*H310 mm Net weight: 184g                      Gross weight: 241g Output: 0-10V signal Max current of signal output: &lt;15mA Static power consumption: &lt;3W  <b>Model: TM120U</b></p>