

**■ Non-isolated internal LED Driver (Low PFC, High PFC, Flicker Free) :**

Model	Photo	Power(W)	Input(V)	Output(V)	Current(mA)	PFC	Dimension(mm)	
LL -T819		9—20W	AC100-260V	DC30-85V	230mA	>0.9	64*W14*H11	<ul style="list-style-type: none"> <li>■Non-isolated</li> <li>■High Frequency Capacitor</li> <li>■2years warranty</li> <li>■Surge Protection 2.5-3KV</li> </ul>
LL -T820		9—20W Flicker Free		DC30-85V	230mA	>0.9	120*W25*H15	
LL -PF2113		9—20W THD<15%		DC30-85V	230mA	>0.9	56*W27*H15	
LL -PF2227		24-28W		DC30-85V	300MA	>0.9	125*W15*H10	
LL -PF2227B		30-36W		DC30-85V	450MA	>0.9	150*W15*H10	
LL -2226B		9—20W	AC170-260V	DC30-85V	230mA	>0.5	64*W14*H11	
LL -QP2118		6-24W	AC100-260V	DC20-85V	300mA	>0.9	42*W24*H13	

**■ Isolated Low PFC internal LED Driver:**

Model	Photo	Power(W)	Input(V)	Output(V)	Current(mA)	PFC	Dimension(mm)	
LL -D03	/	3*1W	AC100-260V	DC6-12V	260-280mA	0.5	23*W16*H13	<ul style="list-style-type: none"> <li>■Isolated Wide Range Input</li> <li>■High Frequency Capacitor</li> <li>■Flicker Free</li> <li>■2years warranty</li> </ul>
LL -D05		1*1W		DC3-4V	280-300mA	0.5	23*W16*H13	
		1*3W		DC3-4V	580-600mA	0.5	23*W16*H13	
		2-5W		DC6-12V	280-300mA	0.5	23*W16*H13	
LL -D07		4-7W		DC12-25V	260-280mA	0.5	30*W15*H14	
LL -D12		8-12W		DC24-42V	280-300mA	0.5	40*W20*H16	
LL -2207B				DC9-18V	580-600mA	0.5		
LL -D18		12-18W		DC36-63V	260-280mA	0.5	47*W22*H15	
LL -2213B		18-24W		DC54-84V	280-300mA	0.5	55*W23*H17	
LL -D30	/	25-30W		DC25-36V	580-600mA	0.5		
				DC36-63V	850-900mA	0.5	71*W22*H16	
LL -D36		25-36W		DC72-126V	280-300mA	0.5	75*W22*H16	
LL -D40		40-50W		DC54-84V	580-600mA	0.5	77*W27*H17	
				DC25-36V	1350-1400mA	0.5		

**■ AC/DC12-24V LED Driver:**

Model	Photo	Power(W)	Input(V)	Output(V)	Current(mA)	PFC	Dimension(mm)	
LL -1203		1-3*1W	AC/DC12V	DC3-12V	300mA±5%	/	13*W18*H12	
		1-3*3W		DC3-12V	600mA±5%	/		
		3-6W	DC24V	DC3-12V	300、600	/		
LL -2407		1-7W	AC/DC24V	DC3-23V	300mA±5%	/	31*W18*H12	<ul style="list-style-type: none"> <li>■Shielded Inductor</li> <li>■Buck</li> <li>■Boost</li> <li>■2years warranty</li> </ul>
		4-6*3W		DC12-24V	600mA±5%	/		
LL -2412		10-12W	AC/DC24V	DC32-42V	300mA±5%	/	38*W23*H15	
		6-9W	AC/DC12V	DC18-32V	300mA±5%	/		
LL -1218		12-18W	AC/DC 12-24V	DC36-63V	300mA±5%	/	42*W25*H17	
		20W		DC25-36V	600mA±5%	/		
LL -1235		30W	DC12-24V	DC25-36V	900mA±5%	/	100*W28*H23	
		50W		DC25-36V	1500mA±5%	/		

**■ Isolated Internal LED Driver (High PFC) :**

Model	Photo	Power(W)	Input(V)	Output(V)	Current(mA)	PFC	Dimension(mm)	
LL -PF2210	/	8-12W MOV	AC100-260V	DC24-42V	300mA±5%	>0.9	48*W24*H14	
				DC9-18V	600mA±5%	>0.9		
LL -PF2216		13-20W MOV		DC36-63V	300mA±5%	>0.9	56*W27*H15	
				DC25-36V	600mA±5%	>0.9		
LL -PF2219		24-36W MOV		DC72-126V	300mA±5%	>0.9	70*W27*H17	
				DC25-36V	900mA±5%	>0.9		
				DC25-42V	600mA±5%	>0.9		
LL -PF2240		40-50W MOV		DC36-63V	600mA±5%	>0.9	87*W31*H22	
				DC54-84V	600mA±5%	>0.9		
				DC25-36V	1500mA±5%	>0.9		