





Lite Lion products including DMX series, DALI series, WIFI series, Intelligent electric series, Dimmer series, RF series, dream color series, indoor and outdoor lighting control system series etc. Please kindly contact us for more details and we will reply a.s.a.p.

<p>1 channel dimmer (Rotating)</p> 	<p>Working temperature: -20-60 °C Supply voltage: DC12-24V Size: L89*W59*H35 mm Package size: L96*W64*H65mm Carton size: L500*W275*H310 mm Net weight: 85g Gross weight: 110g Output: 1 channel Output current : <8A Static power consumption: <1W Output power: 12V< 96W, 24V<192 W Model: XDIMMER-1CH</p>
<p>1 channel dimmer</p> 	<p>Working temperature: -20-60 °C Supply voltage: DC12-24V Size: L61*W33*H32 mm Package size: L105*W65*H40mm Carton size: L500*W275*H310 mm Net weight: 30g Gross weight: 55g Output: 1 channel Maximum load current :2A Static power consumption : <1W Color: white and black one for you to choose Output power: 12V<24W, 24V<48W Model: LDIMMER-1CH</p>
<p>Wall-human body induction switch</p> 	<p>Working temperature: -20-60 °C Supply voltage: DC5V, DC12-24V (order Indicate required voltage) Size: 86*86*26 mm Package size: 160*95*51mm Carton size: L496*W272*H308mm Net weight: 60g Gross weight: 100g Output: 1 channel Induction distance: 5-8m Induction Angle: 120°C Static power : <1W Output current : <8A Output power: 5V<40 W, 12V< 96W, 24V<192 W Model MPIR-1CH</p>

<p>Mini 3key RGB Controller</p> 	<p>Working temperature: -20-60 °C Supply voltage: DC5V-24V Size: 35*15*4.5mm Package size:155*50*3.5mm Net weight: 111g Gross weight: 15g Output: Three CMOS drain open-circuit output connecting mode: common anode Static power: : <0.5W Output current : <2A(each channel) Output power: 5V< 30W, ,12V< 72W, 24V<144W function: realize gradient, fadein dimming, jump, flicker, blasting flash and a variety of static color lighting effects, with easy installation, simple to use etc. Model: TC103</p>
<p>Constant current amplifier</p> 	<p>Work temperature: -20-60°C Supply voltage: DC12-48V Size:105*65*25mm Package size:122*85*42mm Carton size: L500*W275*H310mm Net weight: 115g Gross weight: 145g Output: 3 channel Connecting mode: common anode Static power: <1W Output current:< 350mA(each channel) Output power: 12V< 12.6W, 48V< 50.4W Input / output optical isolation, not common ground Model: ZJFJ-350mA-3CH</p>
<p>Mini 3key Dimmer</p> 	<p>Working temperature: -20-60 °C Supply voltage: DC5V-24V Size: 35*15*4.5mm Package size:185*50mm Net weight: 15.8g Gross weight: 20.1g Output: one CMOS drain open-circuit output connecting mode: common anode Static power: <0.5W Output current : <4A(each channel) Output power: 5V< 20W ,12V< 48W, 24V<96 W function: achieve single way static ten level brightness adjustment, eight monochromatic dynamic model, realize detonation shem, breathing, fadein dimming, strobe, flicker and other kinds of model, also with ten level speed adjustment, speed span easy to carry, simple to use etc. Model: TC101</p>

<p>RF 3key dimmer</p>  A black rectangular LED dimmer with a control panel on top. The panel has three buttons and a small display. The text on the device includes "LED Single Color Dimmer" and "RF-DC12-24V".	<p>Working temperature:-20-60 °C Supply voltage: DC12-24V</p> <p>Size: L110*W56*H34 mm Package size: L145*W95*H50mm</p> <p>Carton size: L500*W275*H310 mm</p> <p>Net weight: 114.4g Gross weight: 153.4g</p> <p>Output: 1 channel Output current : <8A</p> <p>Static power consumption : <1W</p> <p>Output power: 12V< 96W, 24V<192 W</p> <p>Model: DM103</p>
<p>wireless dimmer</p>  A black rectangular LED dimmer with a control panel on top. The panel has three buttons and a small display. The text on the device includes "LED Single Color Dimmer" and "RF-DC12-24V". A black remote control with three buttons and a keychain is shown below the dimmer.	<p>Working temperature: -20-60 °C Supply voltage: DC12-24V</p> <p>Size: L110*W56*H34 mm Package size: L122*W85*H42 mm</p> <p>Carton size: L500*W275*H310 mm</p> <p>Net weight: 78g Gross weight: 103g</p> <p>Output: 1 channel Output current : <8A Static power: <1W</p> <p>Output power: 12V<96W, 24V<192 W</p> <p>Model: RFDIMMER-1CH</p>
<p>12-key Constant Voltage Infrared Dimmer</p>  A white square-shaped infrared dimmer with a circular dial on top. A blue remote control with 12 buttons is shown next to it.	<p>Working temperature: -20-60 °C Supply voltage: DC5V, DC12-24V</p> <p>Size: L87*W87*H42 mm Package size: L160*W95*H51 mm</p> <p>Carton size: L500*W275*H310 mm</p> <p>Net weight: 145g Gross weight: 180g</p> <p>Output: 1 channel Static power: <1W</p> <p>Output current : < 8A</p> <p>Output power: 5V:40W 12V<96W, 24V<192 W</p> <p>Model: MDimmer-IR12B-1CH</p>

<p>1 channel dimmer (Sliding)</p> 	<p>Working temperature: -20-60 °C Supply voltage: DC5V,DC12-24V (order Indicate required voltage) Size: 123*14*26 mm Package size:150*20*50mm Carton size: L496*W272*H308mm Net weight: 25g Gross weight: 40g Maximum load current :4A Output: 1 channel Static power: <1W Output power: 5V<20 W, 12V< 48W, 24V<96 W Function: can realize stepless dimming Model: HDIMMER-1CH</p>
<p>3 channel dimmer (Sliding)</p> 	<p>Working temperature: -20-60 °C Supply voltage: DC12-24V Size: 123*42*27 mm Package size:150*96*52mm Net weight: 80g Gross weight: 120g Carton size: L496*W272*H308mm Maximum load current : 4A(each channel) Output: 3channel Static power : <1W Output power: 5V<72W, 12V<144W, 24V<288 W Function: can realize stepless dimming Model: HDIMMER-3CH</p>
<p>Dimmer (high voltage)</p> 	<p>Working temperature : -20-60 °C Supply voltage: AC90-230V Size: L102*W42*H27 mm Package size: L120*W50*H42 mm Carton size: L500*W275*H310 mm Net weight: 130g Gross weight: 150g Output:: 3 channel(DC90-230V) Connecting mode: common anode Static power: : <1W Output current : <<1.5A (0.5A each channel) Output power: 110V<165W(55W each channel),230V<345W (115W each channel) Model: RFDIMMER-1CH</p>

<p>Touch controller-8key</p> 	<p>working temperature: -20-60℃ supply voltage: DC12V-24V external dimension: L63*W35*H22mm packing size: L105*W65*H40mm net weight: 50g gross weight: 70g output: 3 channels output current: <2A(each channel) connection mode: common anode static power consumption: <1W output power: 12V:<72W, 24V:<144W</p> <p>Model: CON-TRF8B(J)-3CH</p>
<p>Wireless controller</p> 	<p>Work temperature: -20-60℃ Supply voltage: DC5V, 12-24V (order Indicate required voltage) Size: 121*53*25mm Package size: 150*76*51mm Net weight:255g Gross weight: 285g Launch and receive frequency: 433.92MHZ Output: Three CMOS drain open-circuit output Static power: <1W Output current: <4A(each channel) Connecting mode: common anode Output power: 5V:<60W, 12V:<144W, 24V:<288W</p> <p>Model: CON-RF8B(T)-3CH</p>
<p>wireless press dimmer</p> 	<p>Working temperature: -20-60 ℃ Supply voltage: DC12-24V Size:L110*W56*H34mm Package size: L122*W85*H42 mm Carton size: L500*W275*H310 mm Net weight:100g Gross weight: 103g Output:1 channel Output current:<8A Static power: <1W Output power: 5V<40W,12V<96W,24V<192W</p> <p>Model: RFSDIMMER-1CH</p>

<p>DMX amplifier</p> 	<p>Work temperature: -20-60°C Supply voltage:DC5V, 12V-24V (order Indicate required voltage) External dimension: 140*70*50mm Packing size: 150*80*60mm Carton size: L496*W272*H308mm Net weight: 195g Gross weight: 230g Input: DMX signal Output: 1 channel DMX signal</p> <p>Model: DMXZJF-3CH</p>
<p>DMX Multi-channel controller(1:8)</p> 	<p>Work temperature: -20-60°C Supply voltage:DC5V, 12V-24V (order Indicate required voltage) External dimension: 195*93*47 mm Packing size: 232*184*56 mm Carton size: L496*W272*H308mm Net weight: 335g Gross weight: 420g Static power consumption: <5W Input signal: 1 channel DMX signal Output signal: 8 channel DMX signal</p> <p>Model: DMX81</p>
<p>Strip DMX decoder</p> 	<p>Work temperature: -20-60°C Supply voltage: DC5V-24V External dimension:175*53*27mm Packing size: 180*58*55mm Net weight: 300g Gross weight: 350g Output: 3 channel Connection mode: common anode Output current: <5A (each channel) Output power: 5V<75 W, 12V<180W,24V<360W</p> <p>Model: DMX100</p>

<p>Touch Panel Dimmer</p> 	<p>working temperature: -20-60 °C supply voltage: DC12V~24V</p> <p>external dimension: L86*W86*H36 mm</p> <p>packing size:L115*W110*H56 mm</p> <p>Carton size: L500*W275*H310 mm</p> <p>net weight: 126 g gross weigh: 185g output: 1 channel</p> <p>static power consumption: <1W output current: <8A</p> <p>output power: 12V:<96W, 24V:<192W</p> <p>MODEL: TM06</p>
<p>Touch Panel Full-color Controller</p> 	<p>working temperature: -20-60 °C supply voltage: DC12V-24V</p> <p>external dimension: L86*W86*H36 mm</p> <p>packing size: L115*W110*H56 mm</p> <p>net weight: 128g gross weight: 187g output: 3 channels</p> <p>static power consumption: <1W</p> <p>output current: <4A (each channel)</p> <p>output power: 12V:<144W, 24V:<288W</p> <p>MODEL: TM08</p>