







Lite Lion products including DMX series, DALI series, WIFI series, Intelligent electric series, Dimmer series, RF series, dream color series, indoor and outdoor lighting control system series etc. Please kindly contact us for more details and we will reply a.s.a.p.

<p>Wireless multi-channel dimmer</p> 	<p>Working temperature: -20-60 °C    Supply voltage: DC12 -24V Size: L120*W62*H25 mm    Package size: L115*W110*H56mm Carton size: L500*W275*H310 mm Net weight: 133g    Gross weight: 152g Output connection way: common anode 4 channels Max Output current : 4*4A Static power consumption: &lt;1W Max Output power:12V&lt; 192W, 24V&lt;384 W</p> <p><b>Model: DM16</b></p>
	<ol style="list-style-type: none"><li>1.It can control each channel dimming separately, through dimming separately to each channel of controller, can achieve matching of different colors, thus a different color can show up</li><li>2. This controller has high dimming precision, with effect common dimmer can't achieve.</li><li>3. One remote control can control 4 controllers.</li></ol>
<p>2.4G dimmer</p> 	<p>Working temperature: -20-60 °C    Supply voltage: DC5 -24V Size: L120*W62*H27 mm    Package size: L185*W145*H52 mm Carton size: L500*W275*H310 mm Net weight: 220g    Gross weight: 314g Output: 1 channel    Output current : &lt;16A Static power consumption: &lt;1W Output power: 5V&lt;80 W, 12V&lt; 192W, 24V&lt;384 W</p> <p>Function: 1.Each controller only one address code, in order to prevent to control chaos caused by repeated code control. 2.Each controller can also equipped with four remote can realize many controller synchronous control. 3. Used to control with various kinds of led lights for the light source lamps and lanterns, such as: the point light source, soft light, wash the wall lamp, glass curtain wall lamp, etc.; connection is convenient, simple to use etc.</p>

	<p>4.Can realize single control and group control convenient for use.  <b>Model: RF203</b></p>
<p>Wireless high voltage dimmer</p> 	<p>Working temperature: -20-60 °C    Supply voltage: AC90-240V          Size: L132*W45*24mm    Package size: L140*W55*H35 mm          Carton size: L500*W275*H310 mm          Net weight: 90g    Gross weight: 160g          Output: 1 channel    Connection way: common anode          Output current : &lt;1A          Working power consumption: &lt;1W          Output power: AC220V: &lt;220 W  <b>Functions:</b> Plastic casing is safe and beautiful in appearance. The controller can achieve 256 grade dimming, adopt wireless remote control mode, control strategy is simple. User can adjust light to appropriate brightness according to actual need. This product suit for high-voltage lamp strip on every occasions.   <b>Model: DM300</b></p>
<p>LED line touch dimmer</p> 	<p>Working temperature: -20-60 °C    Supply voltage: DC12 -24V          Controller Size: 39*30.8*9mm    Package size: L174*W84mm          Net weight: 26g    Gross weight: 38g          Output: 1 channel    Output current : &lt;6A    Static power: &lt;0.5W          Output power: 12V&lt; 72W, 24V&lt;144 W          Function: Led line touch dimmer adopts capacitive touch technology, ON/OFF and Dimming function can achieve touch, direct current 12/24V directly drive led lighting product, such as led cabinet light, led dome light, LED light bar and led panel light, it can also be used as on/off button, in the dimming, it won't flicker.   <b>Model: DM200</b></p>

<p>Touch 5key dimmer</p> 	<p>Working temperature:-20-60 °C    Supply voltage: DC12-24V                  Size: L84*W64*H23 mm    Package size: L200*W146*H36 mm                  Carton size: L500*W275*H310 mm                  Net weight: 75g    Gross weight: 197g                  Output: 1 channel    Output current : &lt;12A                  Static power consumption: &lt;1W                  Output power: 12V&lt; 120W, 24V&lt;240W</p> <p><b>Model: RF303</b></p>
--	--

## (Triac dimmers)

<p>Infrared 12-Key Triac Dimmer</p> 	<p>Working temperature: -20-60 °C                  Supply voltage: AC90-240V (50Hz/60Hz)                  Dimmer size: W87 * L87 * H47 mm                  Remote size: L86 * W33 * H7 mm                  Packing size: L100 * W100 * H65 mm                  Carton size: L500*W275*H310 mm                  Net weight: 150g    Gross weight: 205g                  Output: 1 channel phase control output    Output current: &lt; 0.15A                  Dimming method: leading-edge dimming                  Maximum output power: 150W</p> <p><b>Model: DM012</b></p>
<p>86 type touch dimmer</p> 	<p>Working temperature: -20-60°C                  Supply voltage: AC90-240V (50Hz/60Hz)                  External dimension: L86*W86*H36 mm                  Packing size: L115*W110*H56 mm                  Carton size: L500*W275*H310 mm                  Net weight: 152 g    Gross weight: 210g                  Output: 1 channel    Static power consumption: &lt;2W                  Dimming method: trailing-edge dimming                  Output power: 110V&lt;110W 220&lt;220W</p> <p><b>Model: TM10</b></p>
<p>Triac touch dimmer</p>	<p>Working temperature: -20-60°C</p>

	<p>Power supply voltage: AC90-240V (50Hz/60Hz) External dimension: L86*W86*H36 mm Packing size: L90*W90*H40 mm Carton size: L500*W275*H310 mm Net weight: 150.1 g                      Gross weight: 221.1g Output: 1 channel                      Static power consumption: &lt;2W Dimming method: trailing-edge dimming Output power: 110V&lt;110W 220&lt;200W <b>Model: TM11</b></p>
<p>European standard touch triac dimmer</p> 	<p>Working temperature: -20-60°C Power supply voltage: AC90-240V (50Hz/60Hz) Single external dimension: L80*W80*H42.8 mm Single packing size: L105*W105*H53 mm Net weight: 129 g                      Gross weight: 180g Output: 1 channel                      Output current: &lt;1A Static power consumption: &lt;2W Dimming methods: trailing-edge dimming Output power: 110V: &lt;110W, 220V:&lt;220W <b>Model: TM11E</b></p>
<p>American standard touch triac dimmer</p> 	<p>Working temperature: -20-60°C    Power supply voltage: AC90-240V Single external dimension: L74*W120*H41.8 mm Single packing size: L145*W99*H53 mm Net weight: 181g                      Gross weight: 238g Output: 1 channel                      Static power consumption: &lt;3W Output current: &lt;1A Dimming methods: trailing-edge dimming Output power: 110V: &lt;110W, 220V:&lt;220W <b>Model: TM11U</b></p>
<p>RF triac dimmer</p> 	<p>Working temperature: -20-60°C Power supply voltage: AC90-240V (50Hz/60Hz) Controller external dimension: L104*W68*H30 mm Remote external dimension: L119.7*W43.2*H16.4 mm packing size: L122*W45*H132mm Carton size: L500*W275*H310 mm Output: 1 channel phase control output Net weight: 150g                      Gross weight: 205g Output current: &lt;1A</p>

	<p>MAX output power: 110V&lt;110W 220V&lt;220W  <b>Model: DM014</b></p>
<p>WIFI triac touch dimmer</p> 	<p>Working temperature: -20-60°C                  Power supply voltage: AC90-240V (50Hz/60Hz)                  External dimension: L86*W86*H37 mm                  Packing size: L90 * W90* H40 mm                  Carton size: L500*W275*H310mm                  Net weight: 160g                      Gross weight: 221g                  Output signal: 1 channel phase control output                  Static power consumption: &lt;2W                  Output current: &lt;200W:    <b>Model: TM111</b></p>
<p>DMX triac dimmer (3 channel)</p> 	<p>Working temperature: -20-60°C                  Power supply voltage: AC90-240V (50Hz/60Hz)                  External dimension: L87*W71*H54 mm                  Packing size: L100*W80*H75 mm                  Net weight: 155g                      Gross weight: 210g                  Output: 3 channels                  Output signal: 1 channel phase control output                  Single channel max output current: &lt;1A (each channel)                  Static power consumption: &lt;3W                  Output power: 110V: &lt;3*110W, 220V: &lt;3*220W    <b>Model: DMX302</b></p>

## ( 0-10V dimmer)

<p>Illumination Compensation Controller</p>	<p>Working temperature: -20-60°C                  Power supply: AC90-240V, 50Hz/60Hz                  External dimension: Φ95 * H45mm                  Packing size: L106 * W106 * H55mm                  Gross weight: 105g                      Net weight: 148g                  Output: 0-10V signal                      Static power consumption: &lt;1.5W                  Light threshold range: 0-1023 lux                  Ham should angle: 120 degree.</p>
---	--

 <p>A white, dome-shaped motion sensor with a blue sensor lens on top and a blue LED indicator on the front.</p>	<p>Delay time range: 6-30s    Sensing distance: 5-8 m Relays power: 5A-250V</p> <p><b>Model: TC500</b></p>
<p>WIFI touch dimmer (output 0-10V)</p>  <p>A black rectangular touch dimmer with a small LCD screen and several touch buttons. Below it, two smartphones are shown with colorful app interfaces and wireless signal waves emanating from them, indicating WiFi connectivity.</p>	<p>Working temperature: -20-60 °C Supply voltage: AC90-240V (50Hz/60Hz) External dimension: L86*W86*H37 mm Package size: L112*W115*H60 mm Carton size: L500*W275*H310 mm Net weight: 160g    Gross weight: 221g Max current of signal output: 15mA Static power consumption: &lt;3W</p> <p><b>Model: TM113</b></p>
<p>European standard touch dimmer (output 0-10V)</p>  <p>A black rectangular touch dimmer with a circular touch pad in the center featuring a power button and directional arrows.</p>	<p>Working temperature: -20-60°C Power supply voltage: AC90-240V (50Hz/60Hz) External dimension: L80*W80*H42 mm Packing size: L105*W105*H53 mm Carton size: L500*W275*H310 mm Net weight: 144g    Gross weight: 194g Output signal : 0-10V signal Max current of signal output: 15mA Static power consumption: &lt;3W</p> <p><b>Model: TM120E</b></p>
<p>America standard touch dimmer (output 0-10V)</p>  <p>A black rectangular touch dimmer with a vertical touch pad and a power button at the bottom.</p>	<p>Working temperature: -20-60°C Power supply voltage: AC90-240V (50Hz/60Hz) External dimension: L74*W120*H42 mm Packing size: L145*W99*H53 mm Carton size: L500*W275*H310 mm Net weight: 184g    Gross weight: 241g Output: 0-10V signal Max current of signal output: &lt;15mA Static power consumption: &lt;3W</p> <p><b>Model: TM120U</b></p>

<p>Touch Panel 0-10V Output Dimmer</p> 	<p>Working temperature: -20-60°C                  Power supply voltage: AC90-240V (50Hz/60Hz)                  External dimension: L86*W86*H36 mm                  Remote size: L119.7*W43.2*H16.4 mm                  Packing size: L195*W155*H60 mm                  Carton size: L500*W275*H310 mm                  Net weight: 154g                      Gross weight: 263g                  Output signal : 0-10V signal                  Max current of signal output: 15mA                  Static power consumption: &lt;3W</p> <p><b>Model: TM016</b></p>
<p>Wireless 0-10V dimmer</p> 	<p>Working temperature: -20-60°C                  Power supply voltage: AC90-240V (50Hz/60Hz)                  Controller external dimension: L103.6*W67.9*H29.7 mm                  Remote external dimension: L119.7*W43.2*H16.4 mm                  Packing size: L122*W45*H130 mm                  Carton size: L500*W275*H310mm                  Net weight: 145g                      Gross weight: 199g                  Output signal : 0-10V signal    0-10v output current: &lt;15mA                  Static power consumption: &lt;3W</p> <p><b>Model: DM015</b></p>
<p>DMX 3CH high-voltage dimmer (output 0-10V)</p> 	<p>Working temperature: -20-60°C                  Power supply voltage: AC90-240V (50Hz/60Hz)                  External dimension: L87*W72*H54 mm                  Packing size: L100*W80*H75 mm                  Net weight: 155g                      Gross weight: 210g                  Output: 3 channels                      Input signal: DMX512 signal                  Output signal : 0-10V signal                  0-10V output current: &lt;15mA/ each channel                  Static power consumption: &lt;3W                      Guide rail size: 35mm</p> <p><b>Model: DMX303</b></p>
<p>Dimmer (input 0-10V)</p>	<p>Working temperature: -20-60 °C                      Supply voltage: DC5-24V</p>



<https://litelion.com>



External dimension: L108 X W42 X H27 mm

Package size: L110 X W50 X H40 mm

Carton size: L500\*W275\*H310 mm

Net weight: 112g      Gross weight: 135g

Input: 0-10v dimmer signal      Output current : <8A

Static power consumption: <1W

Output power: 12V<96W, 24V<192 W

**Model: DM010**